

Serial No. 09/771,389

Page 2

IN THE CLAIMS:

Please amend the claims as follows:

1. (currently amended) A method in a portable subscriber unit for minimizing a connection setup time in a communication network comprising a wide area network, the method comprising the steps of:

maintaining in a memory of the portable subscriber unit a list identifying a plurality of devices which are to be connected quickly through the communication network;

establishing a new connection with the communication network; and

performing, in response to establishing said new connection, when necessary for pre-programming the communication network to minimize the connection setup time for subsequent connections with said plurality of devices, at least one of the steps of:

sending names of the plurality of devices to a domain name server (DNS) of the communication network to obtain Internet Protocol (IP) addresses corresponding to the names, thereby causing the DNS to cache the IP addresses of the plurality of devices for faster servicing of subsequent connections; and

transmitting a dummy ~~Internet Protocol (IP)~~ IP packet to said plurality of devices,

wherein the step of establishing the new connection comprises the steps of:

establishing the new connection via a new local area network (LAN); and

comparing an identifier of the new LAN with a previously stored identifier of a most recently connected old LAN, and

wherein the method further comprises, prior to the performing step, the step of determining that the sending and transmitting steps are not necessary when the identifier of the new LAN is equal to the previously stored identifier of a most recently connected old LAN.

2. (original) The method of claim 1, wherein the performing step comprises the step of performing both the sending step and the transmitting step.

Serial No. 09/771,389

Page 3

3. (original) The method of claim 1, further comprising the step of repeating the performing step with regard to ones of said plurality of devices with which the portable subscriber unit has not communicated for a predetermined length of time.

4. (original) The method of claim 1, wherein the step of maintaining said list comprises the step of identifying a subset of devices with which the portable subscriber unit has recently communicated.

5. (original) The method of claim 1, wherein the step of maintaining said list comprises the step of identifying a predetermined number of devices with which the portable subscriber unit has most frequently communicated over a predetermined time period.

6. (original) The method of claim 1, wherein the step of maintaining said list comprises the step of providing an interface for a user of the portable subscriber unit to specify the plurality of devices which are to be connected quickly through the wide area network.

7. (canceled)

8. (currently amended) The method of ~~claim 7~~ claim 1, further comprising the step of determining that the sending and transmitting steps are not necessary when the comparing step indicates that the new LAN and the old LAN are sub-networks of a single LAN.

9. (currently amended) A portable subscriber unit for minimizing a connection setup time in a communication network comprising a wide area network, the portable subscriber unit comprising:

a processor for controlling the portable subscriber unit, the processor including a memory; and

a communication interface coupled to the processor for communicating with the communication network,

Serial No. 09/771,389

Page 4

wherein the processor is arranged and programmed to:

maintain in the memory a list identifying a plurality of devices which are to be connected quickly through the communication network;

establish a new connection with the communication network; and

perform, in response to establishing said new connection, when necessary for pre-programming the communication network to minimize the connection setup time for subsequent connections with said plurality of devices, at least one of the steps of:

sending names of the plurality of devices to a domain name server (DNS) of the communication network to obtain Internet Protocol (IP) addresses corresponding to the name, thereby causing the DNS to cache the IP addresses of the devices for faster servicing of subsequent connections; and

transmitting a dummy ~~Internet Protocol (IP)~~ IP packet to said plurality of devices,

wherein the processor is further arranged and programmed to:

establish the new connection via a new local area network (LAN); and

compare an identifier of the new LAN with a previously stored identifier of a most recently connected old LAN, and

prior to the performing step, determine that the sending and transmitting steps are not necessary when the identifier of the new LAN is equal to the previously stored identifier of a most recently connected old LAN.

10. (original) The portable subscriber unit of claim 9, wherein the processor is further arranged and programmed to perform both the sending step and the transmitting step.

11. (original) The portable subscriber unit of claim 9, wherein the processor is further arranged and programmed to repeat at least one of the sending and transmitting steps with regard to ones of said plurality of devices with which the portable subscriber unit has not communicated for a predetermined length of time.

Serial No. 09/771,389

Page 5

12. (original) The portable subscriber unit of claim 9, wherein the processor is further arranged and programmed to maintain said list by identifying a subset of devices with which the portable subscriber unit has recently communicated.

13. (original) The portable subscriber unit of claim 9, wherein the processor is further arranged and programmed to maintain said list by identifying a predetermined number of devices with which the portable subscriber unit has most frequently communicated over a predetermined time period.

14. (original) The portable subscriber unit of claim 9, further comprising
a user interface coupled to the processor for interfacing with a user, and
wherein the processor is further arranged and programmed to cooperate with the user interface to maintain said list by allowing a user of the portable subscriber unit to specify the plurality of devices which are to be connected quickly through the wide area network.

15. (canceled)

16. (currently amended) The portable subscriber unit of ~~claim 15~~ claim 9, wherein the processor is further arranged and programmed to determine that the sending and transmitting steps are not necessary when the comparing step indicates that the new LAN and the old LAN are sub-networks of a single LAN.

17. (new) The method of claim 1,
wherein the identifier of the new LAN is an IP subnet identifier of the new LAN,
and
wherein the identifier of the most recently connected old LAN is an IP subnet identifier of the most recently connected old LAN.

18. (new) The portable subscriber unit of claim 9,

Serial No. 09/771,389

Page 6

wherein the identifier of the new LAN is an IP subnet identifier of the new LAN,
and

wherein the identifier of the most recently connected old LAN is an IP subnet
identifier of the most recently connected old LAN.